

**AMENDMENT TO THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (currently amended) A method for communicating information from a sender to a receiver through a network having a first path and a second path comprising:
- receiving an information stream;
  - generating at least a first stream subset of packets and a second stream subset of packets in response to the information stream;
  - establishing path diversity by sending the first stream subset of packets through along the first path; and sending the second stream subset of packets through along the second path; and
  - dynamically changing the path diversity during transmission based on the communication conditions between a sender and a receiver.
2. (currently amended) The method of claim 1 further comprising the steps of:
- receiving the first stream subset of packets;
  - receiving the second stream subset of packets;
  - recovering the information stream based on the first stream subset of packets, the second stream subset of packets, or both the first stream subset of packets and the second stream subset of packets.
3. (currently amended) The method of claim 1 wherein the step of sending the first stream subset of packets through along the first path includes
- identifying the first path by employing a path diversity service; and

wherein the step of sending the second ~~stream subset of packets through~~  
along the second path includes

identifying the second path by employing a path diversity service.

4. (currently amended) The method of claim 1 wherein the step of sending the first ~~stream subset of packets through~~  
along the first path and the step of sending the second ~~stream subset of packets through~~  
along the second path includes

providing a source address, a destination address, a number of paths, the first stream and the second stream to a path diversity aware node;

the path diversity aware node identifying a first path and a second path; and

the path diversity aware node sending the first ~~stream subset of packets through~~  
along the first path and

sending the second ~~stream subset of packets through~~  
along the second path.

5. (original) The method of claim 1 further comprising:

dynamically changing the number of paths based on the communication conditions between the sender and receiver.

6. (original) The method of claim 1 further comprising:

dynamically changing at least one node of the first path or the second path based on the communication conditions between the sender and receiver.

7. (currently amended) The method of claim 1 wherein the network includes a first relay having a first address and a second relay having a second address;

wherein the step of sending the first ~~stream subset of packets through~~  
along the first path includes sending at the first ~~stream subset of packets through~~  
along the first relay by addressing the first ~~stream subset of packets~~  
with the first address; and

wherein the step of sending the second ~~stream subset of packets through~~ along the second path includes sending the second ~~stream subset of packets through~~ along the second relay by addressing the second ~~stream subset of packets~~ with the second address.

8. (currently amended) The method of claim 1 wherein the step of sending the first ~~stream subset of packets through~~ along the first path includes

specifying a first source route for the first ~~stream subset of packets~~; and

sending the first ~~stream subset of packets~~ along the first source route; and

wherein the step of sending the second ~~stream subset of packets through~~ along the second path includes

specifying a second source route for the second ~~stream subset of packets~~;

and

sending the second ~~stream subset of packets~~ along the second source route.

9. (currently amended) The method of claim 8 wherein the first source route ~~and the second source route~~ is one of a loose source route that specifies a subset of nodes of the route and a strict source route that specifies all the nodes of the route; and wherein the second source route is one of a loose source route that specifies a subset of nodes of the route and a strict source route that specifies all the nodes of the route.

10. (original) The method of claim 1 wherein the network is a cellular telephone network, a packet network, an Internet, an Intranet, a local area network, a wireless local area network, a wireless local area conforming to IEEE 802.11 specifications, and a local area network conforming to Bluetooth specifications.

B1  
11. (original) The method of claim 1 wherein the information is one of text information, file information, video information, audio information, voice information, multimedia information, control information, time sensitive information, time-sensitive video information, time-sensitive video information, and time-sensitive voice information, time-sensitive multi-media information, and time-sensitive control information.

12. (currently amended) A system for communicating information through a network comprising:

a sender for receiving an information stream to be communicated;

A2  
a multiple stream generator for generating multiple streams that include at least a first stream and a second stream in response to the information stream; and

a path diversity unit coupled to the multiple stream generator for receiving the first stream and the second stream and for establishing path diversity by sending the first stream through a first path in the network and sending the second stream through a second path in the network;

wherein the path diversity unit dynamically changes the path diversity during transmission based on the communication conditions between the sender and a receiver.

13. (original) The system of claim 12 further comprising:


a receiver for receiving the first stream and receiving the second stream; and

a recovery unit for recovering the information stream based on the first stream, the second stream, or both the first stream and the second stream.

14. (original) The system of claim 12 wherein the network includes a first relay having a first address and a second relay having a second address; and

wherein the path diversity unit sends the first stream through the first relay by addressing the first stream with the first address; and sends the second stream through the second relay by addressing the second stream with the second address.

15. (original) The system of claim 12 wherein the sender includes an IP source router for specifying a first source route for the first stream, sending the first stream along the first source route, specifying a second source route for the second stream, and sending the second stream along the second source route.


 16. (currently amended) The system of claim 15 wherein the first source route ~~and the second source route~~ is one of a loose source route that specifies a subset of nodes of the route and a strict source route that specifies all the nodes of the route; and wherein the second source route is one of a loose source route that specifies a subset of nodes of the route and a strict source route that specifies all the nodes of the route.

17. (original) The system of claim 12 wherein the network is a cellular telephone network, a packet network, the Internet, an Intranet, a local area network, a wireless local area network, a wireless local area conforming to IEEE 802.11 specifications, and a local area network conforming to the Bluetooth specifications.

18. (original) The system of claim 12 wherein the information is one of text information, file information, video information, audio information, voice information, multimedia information, control information, time sensitive information, time-sensitive video information, time-sensitive video information, time-sensitive voice information, time-sensitive multi-media information, and time-sensitive control information.

19. (original) The system of claim 12 wherein the path diversity unit performs sending the first stream and the second stream through a first path and second path, respectively, by employing a path diversity aware node.

20. (currently amended) The system of claim 12 wherein the path diversity unit performs path ~~identification~~ selection by employing a path diversity service; wherein the path diversity service ~~provides a description of the paths to utilize~~ selects a path in response to path parameters.



21. (original) The system of claim 20 wherein the path parameters can include a source address, destination address, number of paths, and quality of service requirements for each path; and wherein the quality of service requirements for each path can include bandwidth, delay and packet loss.

22. (currently amended) The system of claim 12 wherein the path diversity unit specifies ~~the paths by~~ one of ~~specifying~~ all nodes to be traversed and a subset of nodes to be traversed; and wherein the subset of nodes can include one of at least one node in the beginning portion of the path, at least one node in the middle portion of the path, and at least one node in the end portion of the path.

23. (original) The system of claim 12 wherein the path diversity unit dynamically changes at least one node of the first path or second path during transmission in response to communication conditions between the sender and receiver.

24. (original) The system of claim 12 wherein the path diversity unit dynamically changes the number of paths employed during transmission in response to communication conditions between the sender and receiver.

25. (original) The system of claim 12 having multiple paths and multiple streams; wherein the path diversity unit assigns streams to paths in one of a deterministic fashion, random fashion, and pseudo-random fashion.

26. (original) The system of claim 12 further comprising:

at least two different Internet Service Providers for connecting the sender to the network;

wherein the path diversity unit achieves path diversity by sending different streams to each of the different Internet Service Providers.

27. (original) The system of claim 12 further comprising:

at least two different connection technologies for connecting the sender to the network;

wherein the path diversity unit achieves path diversity by sending a first stream through a first connection technology and sending a second stream through a different connection technology.

28. (original) The system of claim 2 wherein the different connection technologies include a satellite link, a wired link, a wireless link, and a cellular link.

Please add the following new claims:

--29. (new) The method of claim 1

allowing an application to specify to one of a sender and a path diversity service at least one QoS parameter for each substream of packets.

30. (new) The system of claim 12 wherein the sender applies one of Forward Error Correction Coding to one of packets sent along one of the paths and across packets sent along multiple paths and interleaving to one of packets sent along one of the paths and across packets sent along multiple paths.

31. (new) The system of claim 12 wherein the first stream and the second stream are dependent on each other; and wherein the sender applies interleaving and Forward Error Correction Coding to one of packets sent along one of the paths and across packets sent along multiple paths.

32. (new) The system of claim 12 wherein the sender employs path-hopping path diversity.

33. (new) The system of claim 32 wherein the path diversity unit assigns streams to paths in one of a deterministic fashion, random fashion, and pseudo-random fashion.

34. (new) The system of claim 13 wherein the receiver can be one of a receiver that has no knowledge about path diversity transmission and a receiver that includes a mechanism for tracking the communication quality of each path and communicating the communication quality of each path to the sender for use in optimizing the transmission.--

---